




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification <sup>6</sup> :</b> <b>A61M 5/00, G01N 33/487 // A61J :</b>	<b>A1</b>	<b>(11) International Publication Number:</b> <b>WO 99/59657</b> <b>(43) International Publication Date:</b> 25 November 1999 (25.11.99)
<b>(21) International Application Number:</b> PCT/DK99/00272 <b>(22) International Filing Date:</b> 19 May 1999 (19.05.99) <b>(30) Priority Data:</b> PA 1998 00714      20 May 1998 (20.05.98)      DK <b>(71) Applicant:</b> NOVO NORDISK A/S [DK/DK]; Novo Allé, DK-2880 Bagsværd (DK). <b>(72) Inventors:</b> LAV, Steffen; Lavendelgangen 50, DK-2700 Brønshøj (DK). MUNK, Jens, Aage; Terkelvej 4, DK-3660 Stenløse (DK). RITSING, Brian; Agerbovej 4, DK-2800 Lyngby (DK). <b>(74) Agent:</b> HOFMAN-BANG & BOUTARD, LEHMANN & REE A/S; Hans Bekkevolds Allé 7, DK-2900 Hellerup (DK).		<b>(81) Designated States:</b> AE, AL, AM, AT, AT (Utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), EE, EE (Utility model), ES, FI, FI (Utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).  <b>Published</b> <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>

**(54) Title:** A MEDICAL APPARATUS FOR USE BY A PATIENT FOR MEDICAL SELF TREATMENT OF DIABETES

**(57) Abstract**

The invention relates to an apparatus for self treatment of diabetes. The apparatus is particularly advantageous by comprising a plurality of devices each of which has its own dedicated function corresponding to a number of acts which a diabetic must perform on himself. The individual devices are mutually interconnectible, and the combination comprises at least a body fluid analyser and a dosing apparatus for administering a predetermined dose of insulin to the patient. Each of the devices may be provided in several sizes so that the user himself may combine the relevant devices of the relevant size with respect to the current need. This reduces the risk of forgetting parts of the equipment, and the confidence of using the equipment is enhanced because it is evident to the user that it is a complete apparatus consisting of unified parts.

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

A medical apparatus for use by a patient for medical self treatment of diabetes

This invention comprises a medical apparatus for use by a patient for medical self treatment of diabetes, the treatment including a first operation and at least a second operation, the apparatus comprising a first device for performing the first operation and a second device for performing the second operation.

10

For a number of years it has been possible to purchase various devices for the treatment of diabetes, e.g. for injecting insulin, for measuring blood sugar (such a device is referred to as BGM below), for withdrawing blood samples, and other accessories, the purpose of which is to enable the patient to nurse his disease discretely and with a high standard of hygiene. Many diabetic patients are elderly people who can easily get insecure with respect to the medical equipment, but also many young people need to assure themselves that the equipment is in order, i.e. that everything is there. Or as one must often say to one's children: You have got it all, haven't you?

15

It has also been attempted to build several of the necessary devices together to a single integral unit, see e.g. US Patent No. 5,536,249. This is not the ideal solution either, because such multi-functional devices are normally difficult to operate. A patient holding a gadget in his hand may not be entirely secure and convinced that he has set the apparatus to precisely the function to be performed by means of programmable computers. The more complicated an apparatus, the greater the risk of malfunction, meaning that two such multi-functional devices should actually be at disposal.

25

30

35

The individual devices may be arranged for various respective functions relevant to the treatment of diabetes, such as: a lancet device, a body fluid analyser, a dosing apparatus for administering a  
5 predetermined dose of medication to the patient. Further, there is a number of other aids which the diabetic patient uses, e.g. test strips for the blood analyser, napkins for wiping off blood, extra insulin carpoule, glucose tablets, waste containers, etc.

10

It is not common to build two individual devices together, as manufacturers within the field have tended to specialize in a single device. However, US Patent No. 4,469,110 discloses a lancet device and a simple form of  
15 BGM (the colorimetric measuring principle) which may be mutually interconnected to a single portable unit.

The object of the invention is to make the individual devices physically interconnectible with a view to  
20 optimizing self-treatment of diabetes.

Another object is to construct the individual interconnectible devices such that the optimum treatment is as independent as possible of the specific situation  
25 of the user.

A further object of the invention is to provide an apparatus of the present type for self-treatment of diseases, where, on one hand, the user is certain that he  
30 has all the devices which will be relevant for a future span of time, and on the other hand, is confident about the use of the apparatus.

The object is achieved by making at least a BGM and an  
35 insulin doser interconnectible to a single device. Precisely this combination promotes the insulin

- treatment, as it will be more obvious to the user to adjust the insulin balance if he has just measured his blood sugar; or if the user knows that he is soon to take insulin, it will be more obvious to check the blood sugar content first. This combination departs from the common view where these two devices do not belong together, presumably because the manufacturers have specialized within either the one or the other device.
- 10 The invention is not restricted to the combination of BGM and insulin doser devices, as these devices may be coupled with other devices which are used in the insulin treatment.
- 15 The fact that the individual devices may be combined so that the apparatus covers precisely a given need, means that the apparatus takes up as little space is possible, it being simultaneously easy, even for visually handicapped users, to identify each individual device, so that they will be quite confident that the units fit together. When the devices fit together physically, the users will also be confident that the e.g. the measuring units used are the same. This improves the confidence of using the apparatus of the invention.
- 25 A blood sugar measuring device normally comprises a temperature monitoring device, and in a preferred embodiment the latter device is arranged such that it is close to the insulin carpoule when the blood fluid analyser and the insulin injecting device are coupled together according to the invention. The temperature monitoring device may hereby be used not only for adjusting the blood sugar measurement, but may also be used to warn the user if the apparatus has been in a too hot environment and the insulin has been destroyed. This

is a particular technical advantage by combining precisely the BGM and the doser.

In addition to the possibility of coupling various devices together as needed, it is also possible for one or more of the devices to have several sizes. This may be relevant particularly for the insulin injecting device and for a storage device, enabling the user to combine precisely the devices of the relevant size which will be needed in a given situation, such as an evening party, a working day, a weekend or on a holiday. The optimum treatment achieved by the apparatus of the invention is hereby more independent of the specific situations in which the user may be, and in which the treatment would be inconvenient with the known separate devices.

In the invention, the devices have their own easily recognisable functions which are well-known to the user. The invention does not exclude the use of others of the user's older (i.e. well-known and secure) devices in combination with the invention, which, however, inspires the user to extend his self-treatment apparatus with units which fit together according to the invention.

Conclusively, it is an essential feature of the invention that the stated advantages are of great importance to the user's perception of and habituation to regarding BGM measurement and insulin dosing as closely unified actions, which results in a better self-treatment.

Figure 1 shows a prior art doser with a conventional cap,

Figure 2 shows a doser and a cap with a BGM attached,

Figure 3 shows a doser and a cap with a BGM and a lancet device attached,

Figure 4 shows a doser and a cap with a BGM, a lancet device and a container for test strips attached,

- 5 Figure 5 shows a cap with a BGM, a lancet device, a test strip container and an additional container together with useful/needed extras,

- 10 Figure 6 shows a cap with BGM, a lancet device, a test strip container and a mini-doser and a half-size container together with useful/needed extras,

- 15 Figure 7 shows a first combination of the items presented in figures 1 - 6,

Figure 8 shows a second combination of the items presented in figures 1 - 6,

- 20 Figure 9 shows a third combination of the items presented in figures 1 - 6,

25 In the following an embodiment of the invention will be described in detail with reference to figures 1 - 6. Figures 7 - 11 show some useful combinations which illustrate the use of the invention.

30 The invention also opens up the possibility of a wide variety of combinations as each of said devices may be provided in several sizes. The preferred insulin dosing device may e.g. be replaced by two insulin injection pens of half the size, and a waste container may be inserted instead of one of these pens.

35 Figure 1 shows a doser 20 and a cap 10. The doser 20 comprises a turning wheel 21 for adjusting, either electronically or manually, the level/amount of

medication to be administered, and a display 22 that shows the currently selected amount of medication to be administered. The doser 20 has processing means and storage facilities, like a CPU and RAM, for storing data, like the time, date and amount of medication of the last couple of administrations. This information can be shown in the display 22 at request. The doser 20 further comprises a carpoule (not shown) that contains the medication, and is fitted with a needle 27 through which the medication is administered. The doser 20 has a transparent window 25 so that the amount of medication left in the carpoule can readily be identified. The cap 10 can be fitted to the doser 20 so that one single compact unit and protection of the doser 20, needle 27, etc. is obtained.

Figure 2 shows a doser 20 which corresponds to the doser in figure 1. Also shown is a cap part 10, and a BGM 30. The invention is based on the circumstance that the doser 20 and the BGM 30 should be used together very frequently, one embodiment of the invention might be a cap where the BGM 30 is an integral part. Another embodiment, which is the one shown in figure 2 and described later, could be one where the BGM 30 can be fitted removable by the locking means 31 to the cap part 10 in such a way that a single unit 35 serving as a cap is formed. This has the advantage that when the cap unit 35 is fitted to the doser 20, one set of parts associated functionally can be obtained in a very compact and convenient form. Another option available to the user by this arrangement is that if in special cases the BGM 30 is not needed in a given situation, the user can simply leave the BGM 30 at home, thereby reducing and keeping the size of the device to an absolute minimum.



The BGM 30 has means 34 for inserting test strips 52 (not shown, see figure 4) containing a sample of blood, for analysis by the BGM 30 by operating the buttons 36. The result of the analysis is shown in the display 32.

5

The cap unit 35 may also be provided with a temperature sensor 12, which determines the outside temperature during operation of the BGM 30. This temperature is needed for the calibration of the BGM 30 prior to the analysis of a blood sample. The temperature sensor 12 could be placed close to the carpoule, so that an additional benefit, apart from being used in the calibration, is achieved when the cap unit 35 is fitted over the doser 20. In this location the sensor 12 can monitor the temperature of the medication contained inside the carpoule. This additional feature is very convenient if the medication is sensitive to temperature and could be ruined or damaged if the temperature of the medication is outside a given interval. Thus the BGM 30 could notify the user if the medication has been exposed to a harmful temperature, which improves the user's safety, especially in the case of the medication being insulin, where the consumption/injection of damaged medicine could cause life-threatening situations.

25

Figure 3 shows a doser 20 and a cap unit 35, preferably comprising the cap 10 and the BGM 30, like the cap unit in figure 2, but with the additional feature of having a lancet device 40 removably attached to the BGM 30 by the locking means 31. This lancet device 40 is used by first loading the lancet device through the grip 44 and then pressing the button 42, which releases the lancet, piercing the skin, so that a blood sample can be obtained. With this inclusion the lancet device 40 is always at hand. This has the advantage that a lancet device 40 always is available, for taking a blood sample

35

and applying it to a test strip 52. The test-strip 52 can then be inserted via the means 34 into the BGM 30, which will start analysing the blood sample and, after completion of the analysis, will show the result in the display 32. It is very useful to have the BGM 30 and the lancet device 40 attached together in one compact unit, since a BGM 30 would not normally be used without the lancet device 40, thereby avoiding the fuss and uncertainty of using multiple devices of perhaps different makes. On the other hand, if the user already has a lancet device and is accustomed to and familiar with the use of this particular lancet device, he can still use this original lancet device and just use the remaining items, which will be a compact set consisting of a doser 20 and a BGM 30; The cost will be reduced hereby.

Figure 4 shows a doser 20 and a cap unit 35 from figure 3, but where the additional feature of a test strip container 50 for the safe keeping/storing of test-strips 52 in the space 55 can be added/attached through locking means 31. With this addition a test strip 52 will always be available. This addition further strengthens the use of the compact unit obtained, when the cap unit 35 is fitted to the doser 20. Now the user can either have a single compact unit where all the means for taking and analysing a blood sample are available, or have an even smaller compact unit with just the items (e.g. doser 20 with a BGM 30 plus either a test strip container 50 or a lancet) that are needed, depending on the specific situation.

Figure 4 shows one of the many possible combinations which may be achieved with the apparatus according to the invention. Other examples of expedient combinations are

shown in figures 7-9. The combination shown in figure 4 has the general advantage that it may induce the user to make some additional blood sugar measurements and possibly regulate with insulin injection when the parts are in an assembled state as one unit. There are also situations in which many blood sugar measurements and injections are required, viz. in connection with so-called insulin analogs which are very rapid action substances, within the order of 10 minutes.

Figure 5 shows a cap unit 35 that corresponds to the cap unit in figure 4. Instead of having a doser 20, there is now provided a container unit 60 with a relative large space 69 for storing the items needed everyday for self-treatment. For a diabetic, e.g. such items could be a napkin 61 for wiping excessive blood after a sample has been taken, a waste container 62 for receiving used items, an extra carpoule 63 which could contain another type of insulin, spare needles 27 for the doser, spare lancets 65 for the lancet device 40, some glucose in the form of glucose tablets 64, etc. In some situations and in certain forms of diabetes, the injection of insulin may be replaced by administration of pills which may be stored in the container, which thus replaces the doser described previously. All these items, or the most relevant ones for a given situation, could be held in the container space 69 for easy retrieval, when needed. Previously the user had to carry a bag for each device (BGM, doser, lancet device, etc.) with the respective accessories. So when the cap unit 35 is fitted to the container unit 60, a single compact, easily portable unit is obtained, which can be customised to meet an individual need for an individual day or situation.

Of course, the individual devices may also be interconnected without the BMG and the doser being

coupled together according to the invention. If the doser 20 is not needed - a diabetic does not always need a doser in all situations, since sometimes he only need to observe the glucose level in his blood and regulate this level through a diet - one compact unit with all necessary items readily available is obtained. If a doser 20 is needed, the doser 20 may be fitted with an ordinary cap 10, and thus there will just be two units that contain everything needed in every situation in a very compact and convenient form.

Figure 6 shows a cap unit 35 and extras 61-65 and 27 corresponding to the unit and extras in figure 5. Also shown is a simple small-sized (e.g. disposable) doser 80 (e.g. an insulin injecting pen) with a turning wheel 85 for adjusting the level/amount of medication to be administered. During the adjustment, a display 84 shows the currently selected amount of medication to be administered. After the appropriate level of medication has been set, the user can press the release button 82, which manually injects/administers the selected amount of medication through the needle 87. The doser 80 further comprises a carpoule (not shown) that contains the medication. The doser 80 has a transparent window 88, so that the amount of medication left in the carpoule readily can be identified. This embodiment also includes a container unit 70, which is half the size of the container unit 60 in figure 5. These small size units 70, 80 can be fitted into the cap unit 35 so thereby forming one compact self-treatment unit.

So with this set of modules an optimal compact set can be customised with the things needed for a given situation. The set can either be configured to meet a situation where all the items are needed, thus ending up with two compact units, namely the doser 20 with an ordinary cap

10 and a cap unit 35 with the large container 60 that contains some or all of the extras 61-65 and 27, or be configured to a minimal set containing just items needed for one single situation, e.g. the small doser 80, the  
5 half-size container 70 fitted into the cap unit 35 with/without the BGM 30, the lancet device 40 and the test strip container 50, depending on the specific situation.

10 Figure 7 shows a combination of the cap 10, the BMG 30 and the storage container 60. Such a combination of devices is relevant e.g. in connection with type 2 diabetics who may take insulin regulating medication in tablet form. Here, the storage container 60 may contain  
15 spare lancets 65 (which may belong to another make of lancet devices, which are not shown in the combination in figure 7), test strips 52, glucose in the form of glucose tablets 64 and the insulin regulating medication in tablet form. Another use of the combination shown in  
20 figure 7 is non-refrigerated storage of extra insulin, the temperature then being monitored by the temperature monitoring device 12.

The combination shown in figure 8 might be called all in  
25 one. The insulin injecting device is replaced by an insulin injecting pen of half the size, which gives room for a container 70 (half as large as the container 60 in figure 7).

30 Figure 9 shows another possible combination, using two insulin injecting pens so that the user may carry rapid action insulin as well as slow action insulin. One of the pens may also contain one of the very rapid action insulin analogs mentioned above. Clearly, the combination  
35 in figure 9 may also be supplemented with a lancet device as shown in figure 8.

It will now be appreciated that there are many possible combinations which allow the user to combine precisely the equipment he needs in a given situation. In the preferred embodiments, the individual devices are combined side by side, and the storage container and the insulin injecting device are shown in the lateral direction in larger or smaller embodiments. Clearly, an apparatus according to the invention may also comprise devices which may be interconnected and varied in the longitudinal direction.

P a t e n t   C l a i m s :  
-----

1. A medical apparatus for use by a patient for medical  
5 self treatment of diabetes, the treatment including a  
first operation and at least a second operation, the  
apparatus comprising a first apparatus for performing the  
first operation and a second apparatus for performing the  
second operation, c h a r a c t e r i z e d in that the  
10 first apparatus and the second apparatus can be  
detachably put together so as to form a single unit  
portable by the patient, and that said apparatuses at  
least comprise a body fluid analyser and a dosing  
apparatus for administering a predetermined dose of  
15 insulin to the patient.

2. A medical apparatus according to claim 1, c h a r -  
a c t e r i z e d in that the body fluid analyser is a  
blood glucose monitor.

20

3. A medical apparatus according to claim 1, c h a r -  
a c t e r i z e d in that the dosing apparatus is an  
insulin injecting device.

25 4. A medical apparatus according to claim 1, c h a r -  
a c t e r i z e d in that the apparatus has storage  
space for storing a supply of lancets for the body fluid  
analyser.

30 5. A medical apparatus according to claim 1, c h a r -  
a c t e r i z e d in that the apparatus has storage  
space for storing a supply of test strips for the body  
fluid analyser.

6. A medical apparatus according to claim 3, c h a r -  
a c t e r i z e d in that the apparatus has storage  
space for storing an extra supply (carpoule) of insulin.

5 7. A medical apparatus according to claim 2 and where the  
blood glucose monitor includes a temperature monitoring  
device, c h a r a c t e r i z e d in that, when the  
blood glucose monitor and the insulin injecting device  
are put together, the temperature monitoring device will  
10 monitor the temperature of the insulin in the insulin  
injecting device.

8. An apparatus according to any of the preceding claims,  
c h a r a c t e r i z e d in that any of the said  
15 devices may occur in different sizes for interconnection  
with other devices.

9. An apparatus according to claim 8, c h a r a c -  
t e r i z e d in that the insulin injecting device  
20 comprises two insulin injecting pens arranged to be  
received as a pair in said cap.

10. An apparatus according to claim 8, c h a r a c -  
t e r i z e d in that it comprises an insulin injecting  
25 pen and a storage device to be received as a pair in said  
cap.






Fig. 1

2/9




Fig. 2

3/9




Fig. 3




Fig. 4




Fig. 5





Fig. 6



**Fig. 7**

8/9




Fig. 8






Fig. 9

## INTERNATIONAL SEARCH REPORT

International application No.

PCT/DK 99/00272

## A. CLASSIFICATION OF SUBJECT MATTER

IPC6: A61M 5/00, G01N 33/487 // A61J

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: A61J, A61M, G01N

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5536249 A (T.CASTELLANO ET AL), 16 July 1996 (16.07.96), abstract  --	1-10
A	WO 9509579 A1 (MUODONMUUTOS OY), 13 April 1995 (13.04.95), abstract  --	1-10
A	US 4469110 A (G.J.SLAMA), 4 Sept 1984 (04.09.84), abstract  -- -----	1-10

☐ Further documents are listed in the continuation of Box C.☒ See patent family annex.

## \* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

28 Sept 1999

Date of mailing of the international search report

29 -09- 1999

Name and mailing address of the ISA/  
Swedish Patent Office  
Box 5055, S-102 42 STOCKHOLM  
Facsimile No. +46 8 666 02 86

Authorized officer

Håkan Sandh /itw  
Telephone No. +46 8 782 25 00

**INTERNATIONAL SEARCH REPORT**  
Information on patent family members

International application No.  
**PCT/DK 99/00272**

Patent document cited in search report			Publication date	Patent family member(s)		Publication date
US	5536249	A	16/07/96	AU	1939395 A	25/09/95
				EP	0749332 A	27/12/96
				EP	0777123 A	04/06/97
				JP	10504729 T	12/05/98
				US	5593390 A	14/01/97
				US	5728074 A	17/03/98
				US	5925021 A	20/07/99
				WO	9524233 A	14/09/95
-----						
WO	9509579	A1	13/04/95	NONE		
-----						
US	4469110	A	04/09/84	AU	8505782 A	06/01/83
				CA	1198955 A	07/01/86
				FR	2508305 A,B	31/12/82
				JP	58025145 A	15/02/83
-----						